

Reference : C-28S29 8F-8R TC

The Fixolite box is a 6 m long prefabricated lintel box designed to receive a closure (roller shutter, BSO, etc.). The box consists of an inverted U-shaped, fire-retardant expanded polystyrene (30 kg/m³ density) shell reinforced with steel mesh. The side walls are fitted with aluminum rails.

High Insulation model box. This high insulation box is today the most efficient lintel box and is particularly suited to the thermal requirements of the market.

| | |
|------------------|--|
| Type | 28S29 |
| Outer rail ref. | 8F |
| Inner rail ref. | 8R |
| Color | Blue polystyrene |
| Compatible cheek | J-28 |
| Certification | CSTB 16-11-634 (translated) |

Thermal conductivity U = 1.14 W/m².K

Thermal resistance* R = 0.88 m².K/W

(*) R: thermal resistance (m².K/W) taking into account a λ coefficient of 0.0374 W/m.K after application of a safety coefficient of 1.15.


| | |
|-----------------------------------|------------------------------------|
| Weight | 6.44 kg/m |
| Reaction to fire | class E (EN ISO 11925-2/EN 13 501) |
| Air permeability | c*3 class |
| Acoustic perf. (Dn _W) | 55 dB |

Box dimensions

| | |
|---------------|--------|
| Width | 280 mm |
| Height | 285 mm |
| Tunnel | 222 mm |
| External side | 33 mm |
| Internal side | 25 mm |

Components

| | |
|---------------------------|------------------|
| Brick (terracotta) | 4.06 kg/m |
| Aluminium (recycl. 85%) | 0.81 kg/m |
| Steel (recycl. 96.5%) | 0.76 kg/m |
| Polystyrene (recycl. 10%) | 0.82 kg/m |
| Total | 6.44 kg/m |



Sides finishing

External side

Brick (terracotta)





Internal side

Ribbed or structured polystyrene



Rail diagram



English version

Version française



2024-04 • Fixolite Disclaimer. The information provided in this technical sheet is for reference only and without warranty of accuracy or completeness. Fixolite disclaims any liability for errors, omissions, or consequences related to the use of this information. Specifications are subject to change without notice.