

**Reference : C-35S30 8-8 NB**

The Fixolite box is a 6 m long prefabricated lintel box designed to receive a closure (roller shutter, BSO, etc.). The box consists of an inverted U-shaped, fire-retardant expanded polystyrene (30 kg/m<sup>3</sup> density) shell reinforced with steel mesh. The side walls are fitted with aluminum rails.

**High Insulation model box.** This high insulation box is today the most efficient lintel box and is particularly suited to the thermal requirements of the market.

Type	35S30
Outer rail ref.	827
Inner rail ref.	827
Finishing	Ribbed polystyrene
Color	Blue polystyrene
Compatible cheek	J-30
Certification	<a href="#">CSTB 16-11-634</a> (translated)
Thermal conductivity	U = 0.48 W/m <sup>2</sup> .K
Thermal resistance*	R = 2.09 m <sup>2</sup> .K/W
(*) R: thermal resistance (m <sup>2</sup> .K/W) taking into account a $\lambda$ coefficient of 0.0374 W/m.K after application of a safety coefficient of 1.15.	
Weight	2.77 kg/m
Reaction to fire	class E (EN ISO 11925-2/EN 13 501)
Air permeability	c*3 class
Acoustic perf. (Dn <sub>w</sub> )	58 dB



**Components**

Aluminium (recycl. 85%)	0.57 kg/m
Steel (recycl. 96.5%)	1.1 kg/m
Polystyrene (recycl. 10%)	1.1 kg/m
-	0.0 kg/m
<b>Total</b>	<b>2.77 kg/m</b>

**Finishing (Ribbed polystyrene)****Box dimensions**

Width	350 mm
Height	295 mm
Tunnel	246 mm
External side	78 mm
Internal side	26 mm

Box shown: C-28S29 8-8E NB

**Rail diagram****English version:**[https://fixolite.eu/doc/C-35S30\\_8-8\\_NB.en.pdf](https://fixolite.eu/doc/C-35S30_8-8_NB.en.pdf)**Version française:**[https://fixolite.eu/doc/C-35S30\\_8-8\\_NB.fr.pdf](https://fixolite.eu/doc/C-35S30_8-8_NB.fr.pdf)

**2024-04 • Fixolite Disclaimer.** The information provided in this technical sheet is for reference only and without warranty of accuracy or completeness. Fixolite disclaims any liability for errors, omissions, or consequences related to the use of this information. Specifications are subject to change without notice.